



MAXAM

MS801



Méret	PR	Típus		Átmérő (mm)	Szélesség (mm)	Mintamélység (mm)	Keréknyomás psi/kPa	Terhelhetőség (kg) Targonca akár 25 km/h	
		Felni	TL/TT					Hajtott kerék	Kormányzott kerék
18x7-8	14	TT	4.33R	465	173	17	130/900	1885	1450
	16	TT	4.33R	465	173	17	145/1000	2145	1650
5.00-8	10	TT	3.00D	467	137	14	145/1000	1415	1090
6.00-9	10	TT	400	546	165	16	125/850	1715	1320
	12	TT	400	546	165	16	145/1000	1885	1450
23x9-10	18	TT	6.50F	584	229	19	130/900	3160	2430
	20	TT	6.50F	584	229	19	145/1000	3445	2650
6.50-10	10	TT	500	594	178	17	112/775	1950	1500
	12	TT	500	594	178	17	140/970	2145	1650
23x10-12	16	TT	8.00G	597	244	20	115/800	3160	2430
	20	TT	8.00G	597	244	20	145/1000	3770	2900
7.00-12	12	TT	500	678	196	17	123/850	2680	2060
	14	TT	500	678	196	17	130/900	2755	2120
27x10-12	16	TT	8.00G	683	254	23	115/800	3900	3000
	18	TT	8.00G	683	254	23	130/900	4225	3250
20	TT	8.00G	683	254	23	145/1000	4615	3550	
	8.15-15 (28x9-15)	14	TT	700	709	18	145/1000	3900	3000
250-15	18	TT	7.50BD	734	249	20	138/950	4745	3650
	20	TT	7.50BD	734	249	20	145/1000	5040	3875
7.00-15	14	TT	5.50BD	762	213	20	135/930	3350	2575
7.50-15	14	TT	6.00BD	813	221	20	135/930	3640	2800
8.25-15	14	TT	6.50	848	244	19	115/800	4225	3250
3.00-15	20	TT	8.00	843	297	24	130/900	6500	5000
	22	TT	8.00	843	297	24	145/1000	6695	5150
9.00-20	14	TT	7.00	1039	262	30	130/900	5850	4500
10.00-20	16	TT	7.50	1077	284	34	130/900	6500	5000
11.00-20	18	TT	8.00	1107	297	36	145/1000	7800	6000
12.00-20	24	TT	8.50	1150	317	38	145/1000	9230	7100
	28	TT	8.50	1150	317	38	150/1030	9490	7300
12.00-24	20	TT	8.50	1249	317	38	145/1000	9750	7500
14.00-24	28	TT	10.00W	1369	376	41	145/1000	13000	10000

